

# BGC/45

## ACCESSORIES

Threaded immersion heater for sealed unvented heating and DHW heating systems. Variable temperature adjustment from approx. 10 °C to 80 °C. The temperature can be limited to 45/60/80 °C. Integral temperature controller with high limit safety cut-out. Heating element and protective pipe material: copper; threaded connection: brass, thread G 1½ with PTFE gasket.

### The main features

For matching to individual usage scenarios

High hot water convenience thanks to powerful heating elements

Variable temperature setting via rotary selector

PRODUCT-NO.: 075115



**BGC 6 kW 500 mm ET**

Product-No.: 003769



Type	BGC 6 kW 500 mm ET	BGC/45
Part no.	003769	075115

## Technical data

Connected load ~ 230 V	2-5,7 kW	2-5,7 kW
Connected load ~ 400 V	6 kW	6 kW
Power supply	1/N/PE, 2/PE, 3/PE	1/N/PE, 2/PE, 3/PE
Rated voltage	230/400 V	230/400 V
Frequency	50/60 Hz	50/60 Hz
Version	Universal flange	Universal flange
IP rating	IP44	IP44
Immersion depth	500 mm	455 mm

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.