

CND 75

CONVECTORS

PRODUCT-NO.: 234813

Treat yourself to warmth twice over

With this product, the warmth reaches you in more ways than one. Since two heating systems are integrated in this direct heating appliance, it not only radiates cosy warmth, but also convects it via the indoor air. As a result, you enjoy a pleasant and comfortable room temperature. The appliance's elegant design ensures that it blends in perfectly with your living environment.

Convenient energy savings Easily set your preferred temperature on the appliance and benefit from greater savings: the wall mounted duo convector automatically lowers the temperature when you leave the room. If you open the windows to let fresh air in, the heater switches off automatically.



The main features

Wall mounted duo convector – ideal as an auxiliary heater or interim heater in spring/autumn

Even, pleasant room air heating

Modern and high grade design

Operating controls with illuminated LCD screen

Weekly timer, frost protection and open window detection

Electronic control unit with presence detection


ON/OFF switch and overheating protection

Permanent connection with FIL control core




CND 100

Product-No.: 234814



CND 150

Product-No.: 234815



CND 200


Product-No.: 234816



| Type | CND 75 | CND 100 | CND 150 |
|----------|--------|---------|---------|
| Part no. | 234813 | 234814 | 234815 |

Technical data

| | | | |
|------------------|-------------|-------------|-------------|
| Power supply | 1/N ~ 230 V | 1/N ~ 230 V | 1/N ~ 230 V |
| Rated voltage | 230 V | 230 V | 230 V |
| Rated current | 3,3 A | 4,3 A | 6,5 A |
| Connected load | 0,75 kW | 1 kW | 1,5 kW |
| IP rating | IP 24 | IP 24 | IP 24 |
| Protection class | II | II | II |
| Colour | white | white | white |
| Setting range | 10 - 30 °C | 10 - 30 °C | 10 - 30 °C |
| Height | 504 mm | 504 mm | 504 mm |
| Width | 675 mm | 790 mm | 1010 mm |
| Depth | 120 mm | 120 mm | 120 mm |
| Weight | 6.70 kg | 7.70 kg | 9.70 kg |



| | |
|----------|---------|
| Type | CND 200 |
| Part no. | 234816 |

Technical data

| | |
|------------------|-------------|
| Power supply | 1/N ~ 230 V |
| Rated voltage | 230 V |
| Rated current | 8,7 A |
| Connected load | 2 kW |
| IP rating | IP 24 |
| Protection class | II |
| Colour | white |
| Setting range | 10 - 30 °C |
| Height | 504 mm |
| Width | 1240 mm |
| Depth | 120 mm |
| Weight | 11.50 kg |

Depth including wall mounting bracket

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.