

# CNS 75 Trend UK

## CONVECTORS

PRODUCT-NO.: 236560

### High on heat, low on space.

Sometimes there's just not much room – even for a heater. That is why this wall mounted convector is very slimline. With a minimal depth, it nevertheless delivers outstanding thermal comfort.

**Enjoy a wide range of benefits.** The convector blends into its surroundings perfectly, efficiently delivering cosy warmth. The comfort functions of the integral controller, such as the weekly timer and open window detection, highlight the efficiency and high quality features of the appliance.

### The main features

Permanent connection with FIL control core

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

Even, quiet, air heating

Metal casing and slimline design

Operating controls with illuminated LCD screen

Weekly timer, frost protection and open window detection

Control unit with self-learning capability: automatic calculation of the preheat time in timer mode

ON/OFF switch and overheating protection

**CNS 50 Trend UK**


Product-No.: 236559

**CNS 100 Trend UK**

Product-No.: 236561

**CNS 150 Trend UK**

Product-No.: 236562

**CNS 250 Trend UK**

Product-No.: 236564



Type	CNS 50 Trend UK	CNS 75 Trend UK	CNS 100 Trend UK
Part no.	236559	236560	236561

## Technical data

Power supply	1/N/PE ~240 V	1/N/PE ~240 V	1/N/PE ~240 V
Rated voltage	240 V	240 V	240 V
Rated current	2,1 A	3,1 A	4,2 A
Connected load	0,5 kW	0,75 kW	1,0 kW
IP rating	IP24	IP24	IP24
Protection class	I	I	I
Colour	alpine white	alpine white	alpine white
Setting range	5-30 °C	5-30 °C	5-30 °C
Height	450 mm	450 mm	450 mm
Width	348 mm	426 mm	426 mm
Depth	100 mm	100 mm	100 mm
Weight	4.00 kg	4.60 kg	4.60 kg



Type	CNS 150 Trend UK	CNS 250 Trend UK
Part no.	236562	236564

### Technical data

Power supply	1/N/PE ~240 V	1/N/PE ~240 V
Rated voltage	240 V	240 V
Rated current	6,3 A	10,4 A
Connected load	1,5 kW	2,5 kW
IP rating	IP24	IP24
Protection class	I	I
Colour	alpine white	alpine white
Setting range	5-30 °C	5-30 °C
Height	450 mm	450 mm
Width	582 mm	894 mm
Depth	100 mm	100 mm
Weight	6.00 kg	9.20 kg

Depth including wall mounting bracket

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.