

# CNS-U 1500 Plus LCD (UK)

CONVECTORS

PRODUCT-NO.: 205870

High on heat, low on space

Sometimes there's just not much room – even for a heater. That is why this wall mounted convector is very slimline. With a minimal depth, it nevertheless delivers outstanding thermal comfort.

Enjoy a wide range of benefits

The convector blends into its surroundings perfectly, effectively delivering cosy warmth. The comfort functions of the integral controller, such as the weekly timer and open window detection, highlight the high quality features of the appliance.



## The main features

Permanent connection with FIL control core

---

Control unit with self-learning capability: automatic calculation of the preheat time in timer mode

---

Metal casing and slimline design

---

Even, quiet, air heating

---

Operating controls with illuminated LCD screen

---

ON/OFF switch and overheating protection

---

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

---

Weekly timer, frost protection and open window detection



| Type     | CNS-U 500<br>Plus LCD (UK) | CNS-U 750<br>Plus LCD (UK) | CNS-U 1000<br>Plus LCD (UK) |
|----------|----------------------------|----------------------------|-----------------------------|
| Part no. | 205867                     | 205868                     | 205869                      |

## Heating output

|                                                          |         |         |         |
|----------------------------------------------------------|---------|---------|---------|
| Rated heating output P <sub>nom</sub>                    | 0.50 kW | 0.75 kW | 1.00 kW |
| Minimum heating output (standard value) P <sub>min</sub> | 0.00 kW | 0.00 kW | 0.00 kW |
| Maximum continuous heating output P <sub>max,c</sub>     | 0.50 kW | 0.75 kW | 1.00 kW |

## Auxiliary power consumption

|                                            |         |         |         |
|--------------------------------------------|---------|---------|---------|
| H rated heating output e <sub>Hmax</sub>   | 0.00 kW | 0.00 kW | 0.00 kW |
| H minimum heating output e <sub>Hmin</sub> | 0.00 kW | 0.00 kW | 0.00 kW |
| Dby mode e <sub>LSB</sub>                  | 0.00 kW | 0.00 kW | 0.00 kW |

## Type of heating output/room temperature control

|                                                          |   |   |   |
|----------------------------------------------------------|---|---|---|
| Single stage heating output, no room temperature control | - | - | - |
| Two or more manual stages, no room temperature control   | - | - | - |
| Room temperature control with mechanical thermostat      | - | - | - |
| With electronic room temperature control                 | - | - | - |
| Electronic room temperature control plus day timer       | - | - | - |
| Electronic room temperature control plus week timer      | x | x | x |

## Other control options

|                                                     |   |   |   |
|-----------------------------------------------------|---|---|---|
| Room temperature control with presence detection    | - | - | - |
| Room temperature control with window open detection | x | x | x |
| With distance control option                        | - | - | - |
| With adaptive start control                         | x | x | x |
| With working time limitation                        | - | - | - |
| With black bulb sensor                              | - | - | - |



| Type     | CNS-U 1500<br>Plus LCD (UK) | CNS-U 2000<br>Plus LCD (UK) | CNS-U 2500<br>Plus LCD (UK) |
|----------|-----------------------------|-----------------------------|-----------------------------|
| Part no. | 205870                      | 205871                      | 205872                      |

## Heating output

|                                                          |         |         |         |
|----------------------------------------------------------|---------|---------|---------|
| Rated heating output P <sub>nom</sub>                    | 1.50 kW | 2.00 kW | 2.50 kW |
| Minimum heating output (standard value) P <sub>min</sub> | 0.00 kW | 0.00 kW | 0.00 kW |
| Maximum continuous heating output P <sub>max,c</sub>     | 1.50 kW | 2.00 kW | 2.50 kW |

## Auxiliary power consumption

|                                            |         |         |         |
|--------------------------------------------|---------|---------|---------|
| H rated heating output e <sub>Hmax</sub>   | 0.00 kW | 0.00 kW | 0.00 kW |
| H minimum heating output e <sub>Hmin</sub> | 0.00 kW | 0.00 kW | 0.00 kW |
| Dby mode e <sub>LSB</sub>                  | 0.00 kW | 0.00 kW | 0.00 kW |

## Type of heating output/room temperature control

|                                                          |   |   |   |
|----------------------------------------------------------|---|---|---|
| Single stage heating output, no room temperature control | - | - | - |
| Two or more manual stages, no room temperature control   | - | - | - |
| Room temperature control with mechanical thermostat      | - | - | - |
| With electronic room temperature control                 | - | - | - |
| Electronic room temperature control plus day timer       | - | - | - |
| Electronic room temperature control plus week timer      | x | x | x |

## Other control options

|                                                     |   |   |   |
|-----------------------------------------------------|---|---|---|
| Room temperature control with presence detection    | - | - | - |
| Room temperature control with window open detection | x | x | x |
| With distance control option                        | - | - | - |
| With adaptive start control                         | x | x | x |
| With working time limitation                        | - | - | - |
| With black bulb sensor                              | - | - | - |



|          |                             |
|----------|-----------------------------|
| Type     | CNS-U 3000<br>Plus LCD (UK) |
| Part no. | 205873                      |

#### Heating output

|                                                          |         |
|----------------------------------------------------------|---------|
| Rated heating output P <sub>nom</sub>                    | 3.00 kW |
| Minimum heating output (standard value) P <sub>min</sub> | 0.00 kW |
| Maximum continuous heating output P <sub>max,c</sub>     | 3.00 kW |

#### Auxiliary power consumption

|                                            |         |
|--------------------------------------------|---------|
| H rated heating output e <sub>Hmax</sub>   | 0.00 kW |
| H minimum heating output e <sub>Hmin</sub> | 0.00 kW |
| Dby mode e <sub>ISB</sub>                  | 0.00 kW |

#### Type of heating output/room temperature control

|                                                          |   |
|----------------------------------------------------------|---|
| Single stage heating output, no room temperature control | - |
| Two or more manual stages, no room temperature control   | - |
| Room temperature control with mechanical thermostat      | - |
| With electronic room temperature control                 | - |
| Electronic room temperature control plus day timer       | - |
| Electronic room temperature control plus week timer      | x |

#### Other control options

|                                                     |   |
|-----------------------------------------------------|---|
| Room temperature control with presence detection    | - |
| Room temperature control with window open detection | x |
| With distance control option                        | - |
| With adaptive start control                         | x |
| With working time limitation                        | - |
| With black bulb sensor                              | - |

Depth including wall mounting bracket

**Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.