

# SHS 1800

STORAGE HEATING

PRODUCT-NO.: 200182

## Slimline design that blends in perfectly

This storage heater integrates extremely well into your living environment. It has such a slimline design that it is eminently suitable for wall mounting. However, the appliance's elegant appearance means it is just as impressive when installed as a floorstanding heater.

## Experience warmth without being wasteful

This storage heater's features are also impressive. Clever functions ensure temperatures that are optimally tailored to your needs. They also enable economical operation. You can enjoy pleasant warmth without worrying.

## The main features

Slimline wall mounted or floorstanding storage heater

Intelligent automatic charging with C-Plus Technology for convenient, energy efficient operation

Integral room temperature controller with weekly timer and open window detection

Easily accessible operating controls with illuminated LCD screen

Long service life

Extremely quiet operation due to low noise crossflow fan

**SHS 1200**

Product-No.: 200181

**SHS 2400**

Product-No.: 200183

**SHS 3000**

Product-No.: 200184

**SHS 3600**

Product-No.: 200185

**SHS 4200**

Product-No.: 200186

**SHS 4800**

Product-No.: 200187



Type	SHS 1200	SHS 1800	SHS 2400
Part no.	200181	200182	200183

## Technical data

Power supply	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated current	1,7 A	2,6 A	3,5 A
Rated connected load	1.20 kW	1.80 kW	2.40 kW
Fuse protection	10 A	10 A	10 A
Operating noise	29 dB(A)	28,5 dB(A)	31 dB(A)
Heat retention capacity	39 %	44 %	46 %
Heating output	480 W	730 W	970 W
Height	546 mm	546 mm	546 mm
Width	580 mm	741 mm	902 mm
Depth	218 mm	218 mm	218 mm
Weight	24 kg	30 kg	37 kg
Weight (incl. bricks)	74 kg	106 kg	138 kg
Number of brick packs	6	9	12
Colour	alpine white	alpine white	alpine white



Type	SHS 3000	SHS 3600	SHS 4200
Part no.	200184	200185	200186

## Technical data

Power supply	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated current	4,3 A	5,2 A	6,1 A
Rated connected load	3.00 kW	3.60 kW	4.20 kW
Fuse protection	10 A	10 A	10 A
Operating noise	32 dB(A)	32 dB(A)	32 dB(A)
Heat retention capacity	48 %	49 %	51 %
Heating output	1170 W	1360 W	1590 W
Height	546 mm	546 mm	546 mm
Width	1063 mm	1224 mm	1385 mm
Depth	218 mm	218 mm	218 mm
Weight	43 kg	50 kg	57 kg
Weight (incl. bricks)	169 kg	201 kg	233 kg
Number of brick packs	15	18	21
Colour	alpine white	alpine white	alpine white



Type	<b>SHS 4800</b>
Part no.	200187

### Technical data

Power supply	1/N/PE, 3/N/PE
Frequency	50/- Hz
Rated current	7,0 A
Rated connected load	4.80 kW
Fuse protection	16 A
Operating noise	32 dB(A)
Heat retention capacity	51 %
Heating output	1800 W
Height	546 mm
Width	1546 mm
Depth	218 mm
Weight	63 kg
Weight (incl. bricks)	265 kg
Number of brick packs	24
Colour	alpine white

Overall depth = 21 mm with wall clearance mesh

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.