

SHS 4200

STORAGE HEATING

PRODUCT-NO.: 200186

Slimline design that blends in perfectly

This storage heater integrates extremely well into your living environment. It has such a slimline design that it is eminently suitable for wall mounting. However, the appliance's elegant appearance means it is just as impressive when installed as a floorstanding heater.

Experience warmth without being wasteful

This storage heater's features are also impressive. Clever functions ensure temperatures that are optimally tailored to your needs. They also enable economical operation. You can enjoy pleasant warmth without worrying.

The main features

Slimline wall mounted or floorstanding storage heater

Intelligent automatic charging with C-Plus Technology for convenient, energy efficient operation

Integral room temperature controller with weekly timer and open window detection

Easily accessible operating controls with illuminated LCD screen

Long service life

Extremely quiet operation due to low noise crossflow fan

**SHS 1200**

Product-No.: 200181

**SHS 1800**

Product-No.: 200182

**SHS 2400**

Product-No.: 200183

**SHS 3000**

Product-No.: 200184

**SHS 3600**

Product-No.: 200185

**SHS 4800**

Product-No.: 200187



| | | | |
|----------|----------|----------|----------|
| Type | SHS 1200 | SHS 1800 | SHS 2400 |
| Part no. | 200181 | 200182 | 200183 |

Technical data

| | | | |
|-------------------------|----------------|----------------|----------------|
| Power supply | 1/N/PE, 3/N/PE | 1/N/PE, 3/N/PE | 1/N/PE, 3/N/PE |
| Frequency | 50/- Hz | 50/- Hz | 50/- Hz |
| Rated current | 1,7 A | 2,6 A | 3,5 A |
| Rated connected load | 1.20 kW | 1.80 kW | 2.40 kW |
| Fuse protection | 10 A | 10 A | 10 A |
| Operating noise | 29 dB(A) | 28,5 dB(A) | 31 dB(A) |
| Heat retention capacity | 39 % | 44 % | 46 % |
| Heating output | 480 W | 730 W | 970 W |
| Height | 546 mm | 546 mm | 546 mm |
| Width | 580 mm | 741 mm | 902 mm |
| Depth | 218 mm | 218 mm | 218 mm |
| Weight | 24 kg | 30 kg | 37 kg |
| Weight (incl. bricks) | 74 kg | 106 kg | 138 kg |
| Number of brick packs | 6 | 9 | 12 |
| Colour | alpine white | alpine white | alpine white |



| | | | |
|----------|----------|----------|----------|
| Type | SHS 3000 | SHS 3600 | SHS 4200 |
| Part no. | 200184 | 200185 | 200186 |

Technical data

| | | | |
|-------------------------|----------------|----------------|----------------|
| Power supply | 1/N/PE, 3/N/PE | 1/N/PE, 3/N/PE | 1/N/PE, 3/N/PE |
| Frequency | 50/- Hz | 50/- Hz | 50/- Hz |
| Rated current | 4,3 A | 5,2 A | 6,1 A |
| Rated connected load | 3.00 kW | 3.60 kW | 4.20 kW |
| Fuse protection | 10 A | 10 A | 10 A |
| Operating noise | 32 dB(A) | 32 dB(A) | 32 dB(A) |
| Heat retention capacity | 48 % | 49 % | 51 % |
| Heating output | 1170 W | 1360 W | 1590 W |
| Height | 546 mm | 546 mm | 546 mm |
| Width | 1063 mm | 1224 mm | 1385 mm |
| Depth | 218 mm | 218 mm | 218 mm |
| Weight | 43 kg | 50 kg | 57 kg |
| Weight (incl. bricks) | 169 kg | 201 kg | 233 kg |
| Number of brick packs | 15 | 18 | 21 |
| Colour | alpine white | alpine white | alpine white |



| | |
|----------|-----------------|
| Type | SHS 4800 |
| Part no. | 200187 |

Technical data

| | |
|-------------------------|----------------|
| Power supply | 1/N/PE, 3/N/PE |
| Frequency | 50/- Hz |
| Rated current | 7,0 A |
| Rated connected load | 4.80 kW |
| Fuse protection | 16 A |
| Operating noise | 32 dB(A) |
| Heat retention capacity | 51 % |
| Heating output | 1800 W |
| Height | 546 mm |
| Width | 1546 mm |
| Depth | 218 mm |
| Weight | 63 kg |
| Weight (incl. bricks) | 265 kg |
| Number of brick packs | 24 |
| Colour | alpine white |

Overall depth = 21 mm with wall clearance mesh

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.