

UPF 40/1-8 E

ACCESSORIES

PRODUCT-NO.: 227413

Energy efficient brine circuit pump ($EEl \leq 0.23$), electronic control, with vapour diffusion-proof thermal insulation.

The main features

Suitable for ground source heat pumps

Integral energy-saving, electronically regulated circulation pump





Type	UPF 30/1-8 E	UPF 30/1-12 E	UPF 40/1-8 E
Part no.	232532	235053	227413

Technical data

Energy Efficiency Index EEI	0,23	0,23	0,23
Power consumption	8-130 W	16-310 W	12-310 W
Fitted length (gauge)	180 mm	180 mm	220 mm
Connection	G 2	G 2	DN 40
Head	8 m	12 m	8 m
Max. throughput	8 m ³ /h	10 m ³ /h	15 m ³ /h
Rated voltage	230 V	230 V	230 V



Type	UPF 50/1-12 E
------	---------------

Part no.	227414
----------	--------

Technical data

Energy Efficiency Index EEI	0,23
-----------------------------	------

Power consumption	25-590 W
-------------------	----------

Fitted length (gauge)	280 mm
-----------------------	--------

Connection	DN 50
------------	-------

Head	12 m
------	------

Max. throughput	29 m ³ /h
-----------------	----------------------

Rated voltage	230 V
---------------	-------

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.