

UP 30/1-8 PCV


ACCESSORIES

PRODUCT-NO.: 235951

The main features

UP 25/7.5 PCV, UP 25/1-8 PCV and UP 30/1-8 PCV with 1500 mm connecting cable

Circulation pump with energy efficiency category A





Type	UP 40/1-8 E	UP 50/1-12 E	UP 25/1-8 PCV
Part no.	227422	227423	235950

Technical data

Energy Efficiency Index EEI	0,23	0,23	0,23
Power consumption	12-310 W	25-590 W	8-130 W
Rated voltage	230 V	230 V	230 V
Fitted length (gauge)	220 mm	280 mm	180 mm
Connection	DN 40	DN 50	G 1 1/2
Head	8 m	12 m	8 m
Max. throughput	15 m ³ /h	29 m ³ /h	8 m ³ /h
Controlled via differential pressure	x	x	x
Control via PWM signal	-	-	x
Controlled via 0-10 V signal with IF module	x	x	-



Type	UP 30/1-8 PCV	UP 25/7.5 PCV
Part no.	235951	201620

Technical data

Energy Efficiency Index EEI	0,23	0,2
Power consumption	8-130 W	10-60 W
Rated voltage	230 V	230 V
Fitted length (gauge)	180 mm	180 mm
Connection	G 2	G 1 1/2
Head	8 m	8,4 m
Max. throughput	8 m ³ /h	4 m ³ /h
Controlled via differential pressure	x	x
Control via PWM signal	x	x
Controlled via 0-10 V signal with IF module	-	-

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.