

# HMS Trend

PRODUCT-NO.: 233826

The hydraulic module simplifies the integration of air source heat pumps into the system hydraulics and is equipped with an appliance cover with high quality paint finish. This allows many components to be installed directly in a single step. The heat pump manager, high efficiency heating circuit pump for heating and DHW, safety valve, expansion vessel and emergency/auxiliary heater are all integrated as standard. An optional insulated connector block can be used, which simplifies installation and reduces installation time.



## The main features

For simplified installation of air source heat pumps

---

Compact design for a small footprint

---

High equipment level through prefabricated hydraulic components

---

Ideal for use in family homes



Type	HMS Trend
Part no.	233826

#### Technical data

Max. permissible pressure	0.30 MPa
External available pressure differential at 1.0 m <sup>3</sup> /h	715 hPa
External available pressure differential at 1.5 m <sup>3</sup> /h	661 hPa
External available pressure differential at 2 m <sup>3</sup> /h	468 hPa
External available pressure differential at 2.5 m <sup>3</sup> /h	300 hPa
Expansion vessel volume	24 l
Rated voltage, control unit	230 V
Rated voltage, emergency/auxiliary heater	230 V
Power consumption, emergency/auxiliary heater	5.90 kW
Height	896 mm
Height incl. connector block	1131 mm
Width	590 mm
Depth	405 mm
Weight	27 kg
Connection	G 1

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.