

HUK 150 Set

ACCESSORIES

PRODUCT-NO.: 203713

The main features

Set with two changeover dampers

Robust design for a long service life

Available for various dimensions



HUK 100 Set

Product-No.: 203711



HUK 125 Set

Product-No.: 203712



HUK 200 Set

Product-No.: 203714



Type	HUK 100 Set	HUK 125 Set	HUK 150 Set
Part no.	203711	203712	203713

Technical data

Connection	DN 100	DN 125	DN 150
kVS value	150 m ³ /h	260 m ³ /h	400 m ³ /h
Leakage rate	tight, leakage rate A (EN 12266-1)	tight, leakage rate A (EN 12266-1)	tight, leakage rate A (EN 12266-1)
Runtime	150 s / 90°	150 s / 90°	35 s / 90°
IP rating	IP54	IP54	IP66
Control	Open/closed	Open/closed	Open/closed
Butterfly valve weight	4 kg	6.7 kg	7.4 kg
Rotary drive weight	4.1 kg	4.1 kg	5.8 kg



Type	HUK 200 Set
Part no.	203714

Technical data

Connection	DN 200
kVS value	820 m ³ /h
Leakage rate	tight, leakage rate A (EN 12266-1)
Runtime	35 s / 90°
IP rating	IP66
Control	Open/closed
Butterfly valve weight	14 kg
Rotary drive weight	5.8 kg

Availability on request

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.