

## HUK 200 Set

ACCESSORIES

PRODUCT-NO.: 203714

### The main features

Set with two changeover dampers

---

Robust design for a long service life

---

Available for various dimensions



**HUK 100 Set**

Product-No.: 203711

---



**HUK 125 Set**

Product-No.: 203712

---



**HUK 150 Set**

Product-No.: 203713



Type	HUK 100 Set	HUK 125 Set	HUK 150 Set
Part no.	203711	203712	203713

## Technical data

Connection	DN 100	DN 125	DN 150
kVS value	150 m <sup>3</sup> /h	260 m <sup>3</sup> /h	400 m <sup>3</sup> /h
Leakage rate	tight, leakage rate A (EN 12266-1)	tight, leakage rate A (EN 12266-1)	tight, leakage rate A (EN 12266-1)
Runtime	150 s / 90°	150 s / 90°	35 s / 90°
IP rating	IP54	IP54	IP66
Control	Open/closed	Open/closed	Open/closed
Butterfly valve weight	4 kg	6.7 kg	7.4 kg
Rotary drive weight	4.1 kg	4.1 kg	5.8 kg



Type	HUK 200 Set
Part no.	203714

### Technical data

Connection	DN 200
kVS value	820 m <sup>3</sup> /h
Leakage rate	tight, leakage rate A (EN 12266-1)
Runtime	35 s / 90°
IP rating	IP66
Control	Open/closed
Butterfly valve weight	14 kg
Rotary drive weight	5.8 kg

Availability on request

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.