

## UPF 30/1-8 E

### ACCESSORIES

Energy efficient brine circuit pump (EEI  $\leq 0.23$ ), electronically controlled, with vapour diffusion-proof thermal insulation.

#### The main features

Reliable and energy efficient brine circulation pump

---

Electronic closed-loop control

---

Insulation shell included in delivery

---

with connecting cable and non-return valve

PRODUCT-NO.: 232532



**UPF 40/1-8 E**

Product-No.: 227413



**UPF 50/1-12 E**

Product-No.: 227414



|          |              |              |               |
|----------|--------------|--------------|---------------|
| Type     | UPF 30/1-8 E | UPF 40/1-8 E | UPF 50/1-12 E |
| Part no. | 232532       | 227413       | 227414        |

## Technical data

|                                          |                        |                         |                         |
|------------------------------------------|------------------------|-------------------------|-------------------------|
| Energy Efficiency Index EEI              | 0.23                   | 0.23                    | 0.23                    |
| Connection                               | G 2                    | DN 40                   | DN 50                   |
| Delivery head                            | 8.00 m                 | 8.00 m                  | 12.00 m                 |
| Max. flow rate                           | 8.00 m <sup>3</sup> /h | 15.00 m <sup>3</sup> /h | 29.00 m <sup>3</sup> /h |
| Power consumption                        | 8-130 W                | 12-310 W                | 25-590 W                |
| Rated voltage                            | 230 V                  | 230 V                   | 230 V                   |
| Control via 0-10 V signal with IF module | -                      | -                       | -                       |
| Control via differential pressure        | x                      | x                       | x                       |
| Control via PWM signal                   | -                      | -                       | -                       |
| Installation length (centre distance)    | 180 mm                 | 220 mm                  | 280 mm                  |

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.