

WPKI-HKM 230 DN 32

ACCESSORIES

PRODUCT-NO.: 209056

The main features

Heating circuit assembly with mixing valve

Complete with high efficiency pump, shut-off valves and gravity valves

Including thermal insulation and wall mounting bracket

Complete with built-in high efficiency pump and 230 V mixer motor

Pump assembly for heating circuit with mixer

**WPKI-HKM 230 DN 25**

Product-No.: 206631

**WPKI-HKM 230 DN 40**

Product-No.: 209057



Type	WPKI-HKM 230 DN 25	WPKI-HKM 230 DN 32	WPKI-HKM 230 DN 40
Part no.	206631	209056	209057

Technical data

Connection, above	G 1	G 1 1/4 I	G 1 1/2 I
Connection, below	G 1 1/2 A	G 2 A	DN 40 PN6
Circulation pump type	Wilo Para SC 25/6-43	Grundfos UPML 32-105 AUTO	Wilo Yonos MAXO plus 40/0.5-12
Height	383 mm	441 mm	816 mm
Width	250 mm	250 mm	320 mm
Depth	245 mm	260 mm	554 mm
Energy Efficiency Index EEI	0.20	0.23	0.20
Delivery head	6.00 m	10.00 m	12.00 m
Max. flow rate	5.70 m ³ /h	11.30 m ³ /h	17.70 m ³ /h

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.