

WPKI-HKM 24 DN 40

ACCESSORIES


PRODUCT-NO.: 206632

The main features

Including thermal insulation and wall mounting bracket

Complete with built-in high efficiency pump and 24 V mixer motor

Pump assembly for heating circuit with mixer



WPKI-HKM 24 DN 32

Product-No.: 206628



Type	WPKI-HKM 24 DN 32	WPKI-HKM 24 DN 40
Part no.	206628	206632

Technical data

Connection, above	G 1 1/4 I	1 1/2 I
Connection, below	G 2 A	DN 40 PN6
Circulation pump type	Grundfos UPML 32-105 AUTO	Wilo Yonos MAXO plus 40/0.5-12
Height	441 mm	811 mm
Width	250 mm	320 mm
Depth	293 mm	554 mm
Energy Efficiency Index EEI	0.20	0.20
Delivery head	10.00 m	12.00 m
Max. flow rate	11.40 m ³ /h	17.70 m ³ /h

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.