

WPL Plus Pack 4

PRODUCT-NO.: 204914

The main features

Separate buffer cylinder for separation of flow rates for maximum operational reliability

High DHW convenience due to separate DHW cylinder

Air source heat pump set for maximum efficiency in new build or modernisation

Mono block heat pump, with its variable speed compressors, ensures perfectly matched heating output and high flow temperatures all year round





Type	WPL Plus Pack 4
Part no.	204914

Technical data

Energy efficiency class, heat pump W35	A++
Energy efficiency class, heat pump W55	A++
Energy efficiency class, composite system (heat pump + controller) W35	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A++
Heating output at A7/W35 (EN 14511)	8.00 kW
Heating output at A2/W35 (EN 14511)	8.33 kW
Heating output at A-7/W35 (EN 14511)	12.86 kW
COP at A7/W35 (EN 14511)	4.82
COP at A2/W35 (EN 14511)	4.14
COP at A-7/W35 (EN 14511)	2.98
SCOP (EN 14825)	4.39
Sound power level (EN 12102)	55 dB(A)
Min./max. application limits for heat source	-20-40 °C
Max. application limit on the heating side	65 °C
Height	1045 mm
Width	1490 mm
Depth	593 mm
Weight	175 kg
Rated voltage, compressor	230 V
Rated voltage, emergency/auxiliary heater	230 V
Refrigerant	R410A

Further information about the set contents can be found under the respective product.

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.