










# WPF 7 basic














BRINE | WATER HEAT PUMPS








PRODUCT-NO.: 230945

## Additional supplies

Article	Part no.	Type	Description
	234762	<b><u>WPKI 6</u></b>	Compact installation
	235199	<b><u>SBPE 400</u></b>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	235949	<b>UP 25/7.5 PCV</b>	Circulation pump
	161696	<b><u>MEG 30</u></b>	Heat transfer medium, 30 litres, Liquid content: 30 l
	233602	<b><u>WPKI-HK E</u></b>	Heating circuit assembly without mixing valve
	233603	<b><u>WPKI-HKM E</u></b>	Heating circuit assembly with mixing valve
	074347	<b><u>WPKI-V</u></b>	Compact installation
	232965	<b><u>SD 25-1 E</u></b>	Pressure hose, angled, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	232968	<b><u>SD 32-1 E</u></b>	Pressure hose, angled, with 30 mm thermal insulation, For pressure hose size DN: 32, Length: 1 m, External diameter with insulation: 106 mm, Connections for the heating and source side: G 1 1/4
	074415	<b><u>SD 25-1</u></b>	Pressure hose, angled, with 19 mm thermal insulation, For pressure hose size DN: 25, Length:

1 m, External diameter with insulation: 80 mm,  
Connections for the heating and source side:  
G 1 1/4

	233711	<b>STB-FB</b>	Safety thermostat, underfloor heating system
	222375	<b><u>WPSB 308 E</u></b>	Brine assembly for the heat source system including high efficiency pump
	232460	<b>WPSV 25-4</b>	Brine distributor DN 20, Number of brine circuits: 4, Ball valve with clamp fitting: DN 20
	230381	<b><u>WPM-RBS</u></b>	Relay set for high efficiency pumps, Height: 211 mm, Width: 205 mm, Depth: 56 mm
	221135	<b><u>WPHW 25</u></b>	Low loss header, Heat pump connection: G 1 1/2, Heating connection: G 1 1/2, Flow rate: 2 m³/h
	221382	<b>DWS1</b>	Brine pressure switch
	230659	<b><u>GWS 1</u></b>	Groundwater module, Height: 630 mm, Width: 640 mm, Depth: 230 mm, Weight: 20,50 kg
	227420	<b><u>HUV 1</u></b>	Heating diverter valve, Connection: G1
	070633	<b><u>WT 10</u></b>	Heat exchanger, Height: 313 mm, Width: 113 mm, Depth: 99.6 mm
	227534	<b><u>SBB 501 WP SOL</u></b>	DHW cylinder, Rated capacity: 495 l, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm
	185443	<b><u>SBP 100</u></b>	Wall mounted buffer cylinder, Rated capacity: 100 l, Depth: 510 mm, Height: 955 mm, Width: 510 mm
	185458	<b><u>SBP 200 E</u></b>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	227590	<b><u>SBP 200 E cool</u></b>	Buffer cylinder, Rated capacity: 207 l, Diameter incl. thermal insulation: 630 mm, Height: 1535 mm

	220824	<b><u>SBP 400 E</u></b>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	227591	<b><u>SBP 400 E cool</u></b>	Buffer cylinder, Rated capacity: 415 l, Diameter incl. thermal insulation: 750 mm, Height: 1710 mm
	185459	<b><u>SBP 700 E</u></b>	Buffer cylinder, Rated capacity: 720 l, Diameter incl. thermal insulation: 910 mm, Height: 1890 mm
	229980	<b><u>SBS 601 W</u></b>	Instantaneous water cylinder, Rated capacity: 613 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229984	<b><u>SBS 601 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 599 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229981	<b><u>SBS 801 W</u></b>	Instantaneous water cylinder, Rated capacity: 759 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm
	229985	<b><u>SBS 801 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 740 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm

**Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance.

Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.