

# WPE-I 59 H 400 Premium

BRINE-WATER HEAT PUMPS

PRODUCT-NO.: 201414

The WPE-I 59 H 400 Premium heat pump provides not only heat, but also DHW convenience. The cascade control can supply both apartment buildings and commercial properties. With its inverter technology, the appliance is exceptionally versatile, and can even be conveniently operated via an app (optional accessory required).

Quiet operation with long service life.

The robust design of the WPE-I 59 H 400 Premium makes it highly reliable, and able to consistently meet the most demanding of output requirements. Despite this, the appliance offers low-noise operation. The practical colour touchscreen facilitates operation.

Efficient DHW generation using hot gas technology.

The hot gas technology allows DHW to be generated during normal heat pump operation – through the use of an auxiliary heat exchanger. The standard equipment configuration provides hot water temperatures efficiently, and at low cost.

## The main features

Inverter technology: Precisely matched to building heat demand

---

Cascade control for powerful heating output

---

Outstanding DHW convenience

---

Hot gas technology as standard

---

Extremely quiet operation





Type	WPE-I 33 H 400 Premium	WPE-I 44 H 400 Premium	WPE-I 59 H 400 Premium
Part no.	201412	201413	201414
Output at B0/W35 (EN 14511)	20.18 kW	26.71 kW	35.60 kW
Heating output at B0/W35 (min/max)	10 - 33 kW	11 - 44 kW	14 - 59 kW
Coefficient of performance at B0/W35 (EN 14511)	4,73	4,6	4,5

## Technical data

Energy efficiency class, heat pump W35	A+++	A+++	A+++
Energy efficiency class, W55 heat pump	A+++	A+++	A+++
SCOP (EN 14825)	5,55	5,65	5,19
Max. heating flow temperature	65 °C	65 °C	65 °C
Max. application limit on the heating side	65 °C	65 °C	65 °C
Sound power level (EN 12102)	41-56 dB(A)	41-56 dB(A)	46-61 dB(A)
Rated compressor voltage	400 V	400 V	400 V
Connection on the heating system side	{35 mm}	{35 mm}	{42 mm}
Connection on the heat source side	{42 mm}	{42 mm}	{54 mm}
Hot gas connection	28 mm	28 mm	28 mm
Height	1723 mm	1723 mm	1742 mm
Width	692 mm	692 mm	900 mm
Depth	803 mm	803 mm	848 mm
Weight	300 kg	300 kg	430 kg



Type	WPE-I 87 H 400 Premium
Part no.	201415
Output at B0/W35 (EN 14511)	52.00 kW
Heating output at B0/W35 (min/max)	21 - 87 kW
Coefficient of performance at B0/W35 (EN 14511)	4,71

#### Technical data

Energy efficiency class, heat pump W35	A+++
Energy efficiency class, W55 heat pump	A+++
SCOP (EN 14825)	5,17
Max. heating flow temperature	65 °C
Max. application limit on the heating side	65 °C
Sound power level (EN 12102)	46-63 dB(A)
Rated compressor voltage	400 V
Connection on the heating system side	{42 mm}
Connection on the heat source side	{54 mm}
Hot gas connection	28 mm
Height	1742 mm
Width	900 mm
Depth	848 mm
Weight	550 kg

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.