

# WPE-I 04 H 230 Premium Pack

PRODUCT-NO.: 204399

## The main features

Mono mode operation possible for heating and DHW thanks to higher flow temperatures

Inverter technology allows ideally matched heating output through the variable speed compressor

- Easy and time saving installation, due to high level of integration and inclusion of accessories
- Buffer cylinder to separate the flows for maximum operational reliability
- Separate DHW cylinder for a high level of DHW convenience





Type	WPE-I 04 H 230 Premium Pack	WPE-I 06 H 230 Premium Pack	WPE-I 08 H 230 Premium Pack
Part no.	204399	204405	204402
<b>Technical data</b>			
Energy efficiency class, heat pump W35	A+++	A+++	A+++
Energy efficiency class, heat pump W55	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	1,96 kW	2,37 kW	2,78 kW
Heating output at B0/W35 (min./max.)	1,0 - 4,2 kW	1,0 - 6,6 kW	1,0 - 7,6 kW
COP at B0/W35 (EN 14511)	4.60	4.60	4.67
SCOP (EN 14825)	5.07	5.20	5.12
Sound power level (EN 12102)	38 - 40 dB(A)	38 - 43 dB(A)	38 - 45 dB(A)
Max. application limit on the heating side	75 °C	75 °C	75 °C
Height	1369 mm	1369 mm	1369 mm
Width	598 mm	598 mm	598 mm
Depth	658 mm	658 mm	658 mm
Weight	180 kg	180 kg	180 kg
Rated voltage, compressor	230 V	230 V	230 V
Rated voltage, emergency/auxiliary heater	230 V	230 V	230 V
Refrigerant	R454C	R454C	R454C
Connection, heating side	28 mm	28 mm	28 mm
Connection, heat source side	28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection



Type	WPE-I 12 H 230 Premium Pack	WPE-I 15 H 230 Premium Pack
Part no.	204407	204404
<b>Technical data</b>		
Energy efficiency class, heat pump W35	A+++	A+++
Energy efficiency class, heat pump W55	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+++	A+++
Heating output at B0/W35 (EN 14511)	4,19 kW	5,18 kW
Heating output at B0/W35 (min./max.)	2,1 - 12,7 kW	2,1 - 14,8 kW
COP at B0/W35 (EN 14511)	5.01	4.86
SCOP (EN 14825)	5.59	5.44
Sound power level (EN 12102)	39 - 46 dB(A)	39 - 47 dB(A)
Max. application limit on the heating side	75 °C	75 °C
Height	1369 mm	1369 mm
Width	598 mm	598 mm
Depth	658 mm	658 mm
Weight	190 kg	190 kg
Rated voltage, compressor	230 V	230 V
Rated voltage, emergency/auxiliary heater	230 V	230 V
Refrigerant	R454C	R454C
Connection, heating side	28 mm	28 mm
Connection, heat source side	28 mm plug-in connection	28 mm plug-in connection

More details regarding set contents can be found under the relevant product

---

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.