

WPE-I 04 HW 230 GB Premium Pack

PRODUCT-NO.: 204400

The main features

Mono mode operation possible for heating and DHW thanks to higher flow temperatures

Inverter technology allows ideally matched heating output through the variable speed compressor

- Easy and time saving installation, due to high level of integration and inclusion of accessories

Easy to transport as the refrigerant circuit and cylinder module can be separated from one another and are fitted with integral carrying handles

- Buffer cylinder to separate the flows for maximum operational reliability





Type	WPE-I 04 HW 230 GB Premium Pack	WPE-I 06 HW 230 GB Premium Pack	WPE-I 08 HW 230 GB Premium Pack
Part no.	204400	204406	204401

Technical data

Energy efficiency class, heat pump W35	A+++	A+++	A+++
Energy efficiency class, heat pump W55	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+++	A+++	A+++
Energy efficiency class, DHW heating with load profile XL	A	A	A
Heating output at B0/W35 (EN 14511)	1,96 kW	2,37 kW	2,78 kW
Heating output at B0/W35 (min./max.)	1,0 - 4,2 kW	1,0 - 6,6 kW	1,0 - 7,6 kW
Nominal capacity	175 l	175 l	175 l
Surface area, heat exchanger	2.10 m ²	2.10 m ²	2.10 m ²
COP at B0/W35 (EN 14511)	4.60	4.60	4.67
SCOP (EN 14825)	5.07	5.20	5.12
Sound power level (EN 12102)	43 - 46 dB(A)	43 - 48 dB(A)	43 - 48 dB(A)
Height	1937 mm	1937 mm	1937 mm
Width	600 mm	600 mm	600 mm
Depth	703 mm	703 mm	703 mm
Weight	265 kg	265 kg	265 kg
Rated voltage, compressor	230 V	230 V	230 V
Rated voltage, emergency/auxiliary heater	230 V	230 V	230 V
Refrigerant	R454C	R454C	R454C



Type	WPE-I 12 HW 230 GB Premium Pack	WPE-I 15 HW 230 GB Premium Pack
Part no.	204403	204408
Technical data		
Energy efficiency class, heat pump W35	A+++	A+++
Energy efficiency class, heat pump W55	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+++	A+++
Energy efficiency class, DHW heating with load profile XL	A	A
Heating output at B0/W35 (EN 14511)	4,19 kW	5,18 kW
Heating output at B0/W35 (min./max.)	2,1 - 12,7 kW	2,1 - 14,8 kW
Nominal capacity	162 l	162 l
Surface area, heat exchanger	3.50 m ²	3.50 m ²
COP at B0/W35 (EN 14511)	5.01	4.86
SCOP (EN 14825)	5.59	5.44
Sound power level (EN 12102)	43 - 49 dB(A)	43 - 49 dB(A)
Height	1937 mm	1937 mm
Width	600 mm	600 mm
Depth	703 mm	703 mm
Weight	275 kg	275 kg
Rated voltage, compressor	230 V	230 V
Rated voltage, emergency/auxiliary heater	230 V	230 V
Refrigerant	R454C	R454C

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.