

WRS STP 12000TL-20

INVERTER

PRODUCT-NO.: 274182

The Sunny Tripower in output ratings from 5 to 12 kW sets new standards for domestic PV systems. Highly flexible thanks to Optiflex and its asymmetric multi-string, it ensures highest yields with its excellent efficiency and Optitrac Global Peak Portal. Apart from communication via the external Bluetooth aerial, a direct connection to Sunny Portal by means of SMA WebConnect also comes as standard - for the first time without datalogger. Furthermore, the "small" Sunny Tripower has integral power supply management functions and facilitates reactive power feed-in.



The main features

Cable connection without tools

Multifunction relay

Bluetooth® communication

Integral web connect function to the Sunny Portal via Ethernet

Three-phase feed-in

Integral grid management functions

Prepared for optimum STIEBEL ELTRON on-site consumption




Type	WRS STP 10000TL-20	WRS STP 12000TL-20	WRS STP5000TL
Part no.	274181	274182	273595
Width	470 mm	470 mm	470 mm
Height	730 mm	730 mm	730 mm
Depth	240 mm	240 mm	240 mm
Weight	37 kg	38 kg	37 kg

Technical data



Type	WRS STP6000TL	WRS STP7000TL	WRS STP8000TL
Part no.	273357	273356	273355
Width	470 mm	470 mm	470 mm
Height	730 mm	730 mm	730 mm
Depth	240 mm	240 mm	240 mm
Weight	37 kg	37 kg	37 kg

Technical data



Type	WRS STP9000TL
Part no.	273354
Width	470 mm
Height	730 mm
Depth	240 mm
Weight	37 kg

Technical data

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.