

STH 720-1 Plus

HEATING BUFFER CYLINDER

PRODUCT-NO.: 203766

The main features

Buffer cylinder for integration into the heating system

Low standby losses thanks to highly effective thermal insulation

Suitable for cooling due to diffusion-proof complete foam application, therefore can be used for heating and cooling

Accessories such as threaded immersion heaters can be installed

Casing can be removed during handling if required





Type	STH 720-1 Plus	STH 210 Plus	STH 415 Plus
Part no.	203766	203763	203764
Rated capacity	703 l	207 l	415 l
Height	1890 mm	1535 mm	1710 mm
Diameter incl. thermal insulation	910 mm	630 mm	750 mm

Technical data

Standby energy consumption/24 h at 65 °C	2,20 kWh	1,10 kWh	1,60 kWh
Connection	4 x G2 A	4 x G2 A	4 x G2 A
Heat exchanger connection	G 1		
Height of unit when tilted	2000 mm	1650 mm	1800 mm
Max. recommended collector aperture area	14 m ²		
Weight	216 kg	58 kg	81 kg



Type	STH 720 Plus
Part no.	203765
Rated capacity	720 l
Height	1890 mm
Diameter incl. thermal insulation	910 mm

Technical data

Standby energy consumption/24 h at 65 °C	2,20 kWh
Connection	4 x G2 A
Heat exchanger connection	
Height of unit when tilted	2000 mm
Max. recommended collector aperture area	
Weight	185 kg

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.